



# CP-WX3014WN

**HITACHI**  
Inspire the Next



## Key Features

- 3,000 ANSI Lumens
- Native WXGA Resolution
- 3000:1 Contrast Ratio
- 7.9 lbs.
- Microphone input with Audio Mixing Capabilities
- Network control, maintenance and security
- Campus Notification System with Audible Alert
- Network Bridge RS232 control
- Lamp life approximately 6,000 Hours (Eco Mode)\*
- Crestron RoomView
- HDMI / Component / Composite / S-Video Inputs
- Stand-by Audio
- 16W Speaker Output
- Template Function
- 2 RGB In, 1 RGB out / Composite / S-Video
- USB connection to computer
- PC-less presentation
- Optional Wireless IEEE802.11b/g/n Ready
- Network Messenger
- Present content via LAN
- 29 dB (Eco Mode)



## Specifications

Model Name	CP-WX3014WN Series	
Liquid Crystal Panel Structure	0.59" polysilicon active-matrix TFT x 3	
Number of Pixels	1024,000 pixels	
Resolution	Video	540 TV lines
	RGB	1280 dots X 800 lines
Colors	16.7 million colors	
Aspect Ratio	Native 16:10	
Lens	Manual zoom x 1.2	
Throw Ratio (distance : width)	1.5-1.8 : 1	
Lamp	210W UHB	
Brightness	3,000 ANSI Lumens	
Color Light Output	3,000 ANSI Lumens	
Expected lamp Life	Approximately 3,000 hours (normal) 6,000 hours (Eco mode)*	
Contrast Ratio	3000 : 1 (using active IRIS)	
Speaker Output	16W (2 x 8W speakers)	
Power Supply	AC100 - 120V / AC220 - 240V 50/60 Hz Power	
Power Consumption	330W	
Operating Temperature	5°C - 35°C (41°F - 95°F)	
Input Signals	RGB	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC 13", MAC 16"
	Composite Video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N
	Component Video	480i, 576i, 480p, 720p, 1080i, 1080p
Acoustic Noise Level	37 dB (30 dB in Eco Mode)	
H-Sync	15 Hz - 106 Hz	
V-Sync	50 kHz - 120 kHz	
Vertical Keystone	+ / - 30°	
Approvals	UL, C-UL, FCC, CE, RoHS	
RGB Input	Analog RGB	15pin Mini-Dsub x 2
RGB Output	RGB	15pin Mini-Dsub x 1
Digital Input		HDMI x 1
Video Input	S-Video	Mini DIN 4-pin connector x 1
	Composite Video	RCA jack x 1
	Component Video	RCA jack x 3
Audio	Input	Stereo Mini jack x 2, RCA(L/R) x 1 pair, Microphone Jack(stereo mini) x 1
	Output	RCA(L/R) x 1 pair
Ethernet		RJ-45 port / 100 base-T
Wireless		Option
Control Terminals		9-pin D-sub connector x 1 (RS-232 control)
Other		USB-A, USB-B (USB Mouse), PC-Less Presentation
Dimensions (W x D x H)		12.5" x 3.9" x 11.3"
Weight		7.9 lbs.
Closed Caption		CC1, CC2, CC3, CC4, T1, T2, T3, T4
Additional Features		Kensington Slot, Digital Gamma Correction, Whiteboard / Blackboard More, Input Source Naming,, MyMemory / MyScreen / MyButtons / MyText, Auto V Keystone, Serial Number on Side, Mac Address on Side
Supplied Accessories		Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual
Optional Accessories		USBWL11N - Wireless USB Key
Lamp		CPX2010LAMP (DT01021)
Remote Control		HLO2771
Filter		MU06481



Screen Size 16:10

Screen Size*		Throw Distance*	
Diagonal*	Width*	Min*	Max*
30	25	37	45
60	51	76	92
80	68	102	123
100	85	128	154
120	102	154	185
150	127	192	232
200	170	257	310
300	254	386	465

Throw Ratio: 1.5 - 1.8:1 (distance : width)

\*Measured in inches

